ENVIRONMENTAL IMPACT ASSESSMENT

A "significant impact" is defined as it is defined in the EIA Regulations (2014): "an impact that may have a notable effect on one or more aspects of the environment or may result non-compliance with accepted environmental quality standards, thresholds or targets and is determined through rating the positive and negative effects of an impact on the environment based on criteria such as by its duration, magnitude, intensity or probability of occurrence". The objective of this EIA methodology is to serve as framework for accurately evaluating impacts associated with current or proposed activities in the biophysical, social and socio-economical spheres. It aims to ensure that all legal requirements and environmental considerations are met in order to have a complete and integrated environmental framework for impact evaluations.

1. IMPACT ASSESSMENT METHODOLOGY

The process of determining impacts to be assessed is one of the most important parts of the environmental impact assessment process. It is of such high importance because the environmental impacts identified can and are often linked to the same impact stream.

In this method all impacts on the biophysical environment are assessed in terms of the overall integrity of ecosystems, habitats, populations and individuals affected. The Environmental Impact Assessment (EIA) 2014 Regulations promulgated in terms of Sections 24 (5), 24M and 44 of the National Environmental Management Act (NEMA) (Act No. 107 of 1998) [as amended] requires that all identified potential impacts associated with the proposed project be assessed in terms of their overall potential significance on the natural, social and economic environments.

The criteria identified in the EIA Regulations (2014) include the following:

- Nature of the impact;
- Extent of the impact;
- Duration of the impact;
- Frequency of the Impact;
- Probability of the impact occurring;
- Degree to which impact can be reversed;
- Degree to which impact may cause irreplaceable loss of resources;
- Degree to which the impact can be mitigated; and
- Cumulative impacts.

Greenmined Environmental has developed an impact assessment methodology (as defined below) whereby the significance of a potential impact is determined through the assessment of the relevant temporal and spatial scales determined of the extent, magnitude and duration criteria associated with a particular impact.

This method does not explicitly define each of the criteria but rather combines them and results in an indication of the overall significance.

DEFINITIONS AND CONCEPTS:

Environmental significance:

The concept of significance is at the core of impact identification, evaluation and decision-making. The concept remains largely undefined and there is no international consensus on a single definition. The following common elements are recognised from the various interpretations:

- Environmental significance is a value judgement;
- The degree of environmental significance depends on the nature of the impact;
- The importance is rated in terms of both biophysical and socio-economic values; and
- Determining significance involves the amount of change to the environment perceived to be acceptable to affected communities.

Significance can be differentiated into impact magnitude and impact significance. Impact magnitude is the measurable change (i.e. intensity, duration and likelihood). Impact significance is the value placed on the change by different affected parties (i.e. level of acceptability) (DEAT (2002) Impact Significance, Integrated Environmental Management, Information Series 5).

The concept of risk has two dimensions, namely the consequence of an event or set of circumstances, and the likelihood of particular consequences being realised (Environment Australia (1999) Environmental Risk Management).

1.1. Nature of the impact

The nature of an impact can be defined as "a brief description of the impact being assessed, in terms of the proposed activity or project, including the socio-economic or environmental aspect affected by this impact".

1.2. Extent of the impact

The extent of an impact can be defined as "a brief description of the spatial influence of the impact or the area that will be affected by the impact".

Table 1: Determining the extent of an impact

	Footprint	Only as far as the activity, such as footprint occurring within the total site area							
EXTENT	Site	Only the site and/or 500m radius from the site will be affected							
Extent or spatial	Local	Local area / district (neighbouring properties, transport routes and adjacent towns) is affected							
influence of impact	Region	Entire region / province is affected							
	National	Country is affected							

1.3. Severity of the impact

Severity relates to the nature of the event, aspect or impact to the environment and describes how severe the aspects impact on the biophysical and socio-economic environment.

Table 2: Rating of Severity

Type of criteria	Rating	Rating													
	1	2	3	4	5										
Quantitative	0-20%	21-40%	41-60%	61-80%	81-100%										
Qualitative	Insignificant / Non-harmful	Small / Potentially harmful	Significant/ Harmful	Great/ Very harmful	Disastrous Extremely harmful										
Social/ Community response	Acceptable / I&AP satisfied	Slightly tolerable / Possible objections	Intolerable/ Sporadic complaints	Unacceptable / Widespread complaints	Totally unacceptable / Possible legal action										
Irreversibility	Very low cost to mitigate/ High potential to mitigate impacts to level of insignificance/ Easily reversible	Low cost to mitigate	Substantial cost to mitigate/ Potential to mitigate impacts/ Potential to reverse impact	High cost to mitigate	Prohibitive cost to mitigate/ Little or no mechanism to mitigate impact Irreversible										
Biophysical (Air quality, water quantity and quality, waste production, fauna and flora)	Insignificant change / deterioration or disturbance	Moderate change / deterioration or disturbance	Significant change / deterioration or disturbance	Very significant change / deterioration or disturbance	Disastrous change / deterioration or disturbance										

1.4. Duration of the impact

Duration refers to the amount of time that the environment will be affected by the event, risk or impact, if no intervention e.g. remedial action takes place.

Table 3: Rating of Duration

Rating		Description
1	Very Short Term	Up to three months (quarter) after construction
2	Short Term	Three months to one year after construction
3	Medium Term	One year to six years after construction
4	Long Term	Six to ten years after construction
5	Permanent	Beyond ten years after construction

1.5. Probability of the impact occurring

The probability of an impact can be defined as "the estimated chance of the impact happening". Probability refers to how often the activity or aspect has an impact on the environment.

Table 4: Determining the probability of an impact

	1	Almost never / almost	Impossible to occur (0 - 20% probability of						
		impossible	occurring)						
	2	Very seldom / highly unlikely	Unlikely to occur (20 -40% probability of occurring)						
PROBABILITY	3	Infrequent / unlikely / seldom	May occur (40-60% chance of occurring)						
	4	Often / regularly / likely / possible	Likely to occur (60-80% chance of occurring)						
	5	Daily / highly likely / definitely	Will certainly occur (80-100% chance of occurring)						

1.6. Degree to which impact can be reversed

The reversibility of an impact can be defined as "the ability of an impact to be changed from a state of affecting aspects to a state of not affecting aspects".

Table 5: Determining the reversibility of an impact

	Reversible	Impacts can be reversed through the implementation of mitigation measures										
REVERSIBILITY												
	Irreversible	Impacts are permanent and can't be reversed by the										
	liteversible	implementation of mitigation measures										

1.7. Determination of Likelihood:

The irreplaceability (likelihood) of an impact can be defined as "the amount of resources that can/can't be replaced". The determination of likelihood is a combination of Frequency and Probability. Each factor is assigned a rating of 1 to 5, as described below and in tables 6 and 7.

1.8. Overall Likelihood

Overall likelihood is calculated by adding the factors determined above and summarised below, and then dividing the sum by 2.

Example of calculating Overall Likelihood

Consequence	Rating
Duration	Example 4
Probability	Example 2
SUBTOTAL	6
TOTAL LIKELIHOOD	2
(Subtotal divided by 2)	3

Determination of Frequency

Frequency refers to how often the specific activity, related to the event, aspect or impact, is undertaken. **Rating of Frequency:**

Rating	Description
1	Once a year or once/more during operation
2	Once/more in 6 Months
3	Once/more a Month
4	Once/more a Week
5	Daily

1.9. Determination of Overall Environmental Significance:

The environmental significance assessment methodology is based on the following determination:

Environmental Significance = Overall Consequence X Overall Likelihood

The multiplication of overall consequence with overall likelihood will provide the environmental significance, which is a number that will then fall into a range of **LOW**, **LOW-MEDIUM**, **MEDIUM**, **MEDIUM-HIGH** or **HIGH**, as shown in the table below.

Significance or Risk	Low	Low-Medium	Medium	Medium-High	High
Overall Consequence					
X	1 - 4.9	5 - 9.9	10 - 14.9	15 – 19.9	20 - 25
Overall Likelihood					

Based on the above, the significance rating scale has been determined as follows:

High

Of the highest order possible within the bounds of impacts which could occur. In the case of negative impacts, there would be no possible mitigation and / or remedial activity to offset the impact at the spatial or time scale for which it was predicted. In the case of positive impacts, there is no real alternative to achieving the benefit.

Medium-High

Impacts of a substantial order. In the case of negative impacts, mitigation and / or remedial activity would be feasible but difficult, expensive, time-consuming or some combination of these. In the case of positive impacts, other means of achieving this benefit would be feasible, but these would be more difficult, expensive, time-consuming or some combination of these.

Medium

Impact would be real but not substantial within the bounds of those, which could occur. In the case of negative impacts, mitigation and / or remedial activity would be both feasible and fairly easily possible, in case of positive impacts; other means of achieving these benefits would be about equal in time, cost and effort.

Low-Medium

Impact would be of a low order and with little real effect. In the case of negative impacts, mitigation and / or remedial activity would be either easily achieved of little would be required, or both. In case of positive impacts alternative means for achieving this benefit would likely be easier, cheaper, more effective, less time-consuming, or some combination of these.

Low

Impact would be negligible. In the case of negative impacts, almost no mitigation and or remedial activity would be needed, and any minor steps, which might be needed, would be easy, cheap and simple. In the case of positive impacts, alternative means would almost all likely be better, in one or a number of ways, than this means of achieving the benefit

Insignificant

There would be a no impact at all – not even a very low impact on the system or any of its parts.

1.10. Determination of Overall Consequence

Consequence analysis is a mixture of quantitative and qualitative information and the outcome can be positive or negative. Several factors can be used to determine consequence. For the purpose of determining the environmental significance in terms of consequence, the following factors were chosen: **Severity/Intensity, Duration and Extent/Spatial Scale**. Each factor is assigned a rating of 1 to 5, as described in the tables above.

1.11. Degree to which the impact can be mitigated

The degree to which an impact can be mitigated can be defined as "the effect of mitigation measures on the impact and its degree of effectiveness".

Table 6: Determining the mitigation rating of an impact

	MITIGATED	High	Impact 100% mitigated
MITIGATION	Degree impact	Medium	Impact >50% mitigated
RATING	can be mitigated	Low	Impact <50% mitigated

1.12. Cumulative Impacts

The effect of cumulative impacts can be described as "the effect the combination of past, present and "reasonably foreseeable" future actions have on aspects".

Table 7: Determining the confidence rating of an impact

CUMUL ATIVE	CUMULATIVE	Low	Minor cumulative effects					
CUMULATIVE RATING	EFFECTS	Medium	Moderate cumulative effects					
KATIKO	LITEOIS	High	Significant cumulative effects					

2. The positive and negative impacts that the proposed activity will have on the environment and the community that may be affected.

No other alternative sites needed to be investigated as this is an amendment of the current EMPR.

The site was identified during the assessment phase of the environmental impact assessment (2014 assessment), by the applicant and project team, and was therefore selected as the **preferred alternative** due to the following:

Positive Impacts:

- The mining site offers the mineral sought after;
- The proposed footprint area was previously used for mining therefore very little indigenous vegetation needs to be disturbed in order to establish the mining area;
- The site is located within neighbouring sand mines, and will minimally affect the community with regards to dust and noise;

- The mineral to be mined is already in sand form and will not need to be blasted in order to loosen the material:
- The mining area can be reached by an existing farm access road that connects to Vaal Eden-Barrage road. No new road infrastructure need to be constructed;
- Due to the small size of the activity and the remote location of the mining area the potential impacts on the surrounding environment, associated with mining is deemed to be of low significance; and
- No residual waste as a result of the mining activity will be produced that needs to be treated on site. Any general waste that may be produced on-site will be contained in sealed refuse bins to be transported to the local municipal landfill site (Parys). The amount of hazardous waste to be produced at the site will be minimal and will mainly be as a result of accidental leakage. Contaminated soil will be removed to the depth of the spillage and contained in sealed bins until removed from site by a hazardous waste handling contractor to be disposed of at a registered hazardous waste handling site.

Negative Impacts:

- Due to the remote location of the mining area very little negative impacts on the community could be
 identified that were deemed to be of significant importance. The dust and noise impacts that may
 emanate from the mining area during the operational phase could have a negative impact on the
 surrounding community if the mitigation measures proposed in this document is not implemented and
 managed on-site; and
- Negative impacts with regard to the environment include potential contamination of the area due to spillage of hydrocarbon products.

The land is currently under cultivated grazing and mixed farming. Two farm houses, a barn and outbuildings are currently present on site. These buildings will not be impacted by mining and are situated in the exclusion zones on the mining plan.

Table 8: Impact Assessment of Bloemhof Quarry

Nature of Impact	Impact	Positive/Nega		Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
	ION / SITE ESTABLISHMEN			1001																		
ACTIVITY:	DEMARCATION OF SITE No impact could be identified other than the beacons being outside the boundaries of the approved processing area.	Neg										Low	Demarcation of the site will ensure that all employees are aware of the boundaries of the processing area and that work stay within approved area.									Low
ACTIVITY:	ESTABLISHMENT OF TE	MPOR	ARY BUILDI	NGS	AND	INFR	AST	RUC	TURE	WIT	HIN BO	UNDARIE	S OF SITE.									
	If the infrastructure is established within the boundaries of the approved mining area, no impact could be identified.	Neg										Low	None.									Low
Social & Safety	Influx of unsuccessful job seekers which may informally settle in area. Potential danger to surrounding communities	Neg	Reversible	1	3	5	3	3	5	4	12	Med	Ensure advertising is limited to local and regional areas, and only specifically advertise for Jobs nationally if skills are not available. Ensure that all power-related structures are adequately marked with relevant signs and warnings and fenced off.	1	2	5	2,7	2	5	3,5	9,333	Low- Med
Hazardous Waste	Contamination of area with hydrocarbons or hazardous waste materials	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Contamination of surface or groundwater due to hazardous spills not cleaned: • Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to ensure proper disposal. • Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at		3	4	2,7	2	5	3,5	9,333	Low- Med

Environmental Impact Assessment

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													 a recognized facility. Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed. Suitable covered receptacles must be available at all times and conveniently placed for the disposal of waste. Non-biodegradable refuse such as glass bottles, plastic bags, metal scrap, etc., must be stored in a container with a closable lid at a collecting point, collected on a weekly basis, and disposed of at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. Biodegradable refuse generated must be handled as indicated above. 									
Geology	Disturbance of geological strata	Neg	Irreversible	1	3	5	3	5	5	5	15	Medium -High	None.	1	3	5	3	5	5	5	15	Medium- High

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles	1	3	4	2,7	2	4	3	8	Low-Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Flora	Loss of biodiversity.	Neg	Reversible	1	2	4	2,3	3	5	4	9,333		and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water system. o Dirty water must be prevented from spilling or seeping into clean water systems. o Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into the storm water management. Ensure permits are obtained to	1	4	2	2,3	2	3	2,5	5,833	Low-
. 1010	Potential damage to vegetation in neighbouring areas.	. 109	. to voi oi oi o		_		2,0				0,000	Med	remove protected species. Relocate all protected species with aid of specialists. Only remove species in areas	•		_	2,0	_		2,0	5,555	Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
	Alien invasive encroachment												designated for activity and do not disturb surrounding areas. Plan activities carefully so that only vegetation that needs to be impacted is impacted. Incorporate herbaceous vegetation into soil stockpiles to maintain a seed bank. Limit activity to area of disturbance and revegetated impacted areas as soon as possible. Eradicate and control all alien invasive species on site. Rehabilitate and revegetated all areas where alien invasive species were removed. Management of weed- or invader plants: • A weed and invader plant management plan must be implemented at the site to ensure eradication of all listed invader plants in terms of the National Environmental Biodiversity Act [NEMBA] (Act No. 10 of 2004) Alien and Invasive Species Regulation GNR 598 and 599 of 2014. • Management must take responsibility to control declared invader or exotic species on the habilitated areas. The following control methods can be used: o "The plants can be uprooted, felled or cut off and can be destroyed completely." o "The plants can be treated with an herbicide that is registered for use in connection therewith and in accordance with the directions for the use of such an herbicide." • The temporary topsoil stockpiles needs to be kept free of weeds.									
Topography	Alteration of topography	Neg	Irreversible	1	2	5	2,7	2	5	3,5	9,333	B Low Med	· • · ·	1	2	5	2,7	2	3	2,5	6,667	Low- Med

Nature of Impact	Impact	Positive/Nega iive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance		Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Land Use	Veldt fire might seriously impact on surrounding land-use (livestock/irrigation of neighbouring farmers). Degrading of grazing potential for livestock farming	Neg	Reversible	1	2	2	1,7	3	5	4	6,66	67 I	Low- Med	Precautionary measures such as fire breaks would be taken into account and the company will join the local FPA. Should it be found that after mining operation have ceased, that the natural vegetation of the area is unacceptable, the area would be revegetated with an indigenous s grass seed mix.	1	2	2	1,7	3	3	3	5	Low- Med
Visual aspect	Deterioration in visual aesthetics of the area	Neg	Reversible	2	1	3	2	2	5	3,5	7		Low- Med	Visual Mitigation: The site must have a neat appearance and be kept in good condition at all times. The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.	2	1	3	2	2	3	2,5	5	Low- Med
Archaeological & cultural sites	Loss of and disturbance to surface archaeological sites	Neg	Irreversible	1	5	5	3,7	1	5	3	11	1	Med	Should artefacts or archaeological items be observed, then all activity should cease immediately, the area marked off and a specialists	1	5	5	3,7	1	3	2	7,333	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation consulted prior to any further	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg	Reversible	1	2	4	2,3	5	5	5	11,67	7 Medium	activity. Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.	1	1	3	1,7	2	3	2,5	4,167	Low
Air quality	Dust nuisance caused by the disturbance of soil.	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Medium	-	2	2	1	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													generated above acceptable limits. Roads will be sprayed with water regularly ,especially during times of high dust generation.									
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Medium	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low
Fauna	Alienation of animals from the area. Potential risk to avifauna. Potential harm through littering. Loss of food, nest sites and refugia Hindrance to nocturnal animals and change in behaviour of nocturnal prey and predators. New habitat available to fauna in the area and reduced activity should result in influx of animals to the area. Impact to nocturnal insects and their predators and other nocturnal animals.	Neg	Reversible	2	2	4	2,7	3	5	4	10,67	Med	Inform staff, contractors and visitors to not harm fauna in the area. Consider the use of bird flappers and balls on the power lines to reduce risk of birds colliding with power lines. Relocate larger animals with the aid of specialists. Ensure relevant permits are in place. Utilize directional lighting and use yellow and orange lighting where possible to reduce impacts on insects. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Conduct annual surveys to monitor faunal biodiversity. Negative impact on fauna that may	2	2	4	2,7	2	5	3,5	9,333	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Conseduence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													enter the area: • The site manager must ensure that no fauna is caught, killed, harmed, sold or played with. • Workers must be instructed to report any animals that may be trapped in the working area. • No snares may be set or nests raided for eggs or young.									
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	3	3	4	3,3	2	1	1,5	5	Low-Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.	3	2	4	3	1	1	1	3	Low

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Ouration	Consequence	Probability	-requency	-ikelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Ouration	Consequence	Probability	-requency	_ikelihood	Significance	Mitigation Rating
Groundwater	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	2	3	3	2,7	3	5	4	10,67	Med	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	2	1	2	1,7	2	3	2,5		Low
	: ABLUTION FACILITIES																		,			
Groundwater	Portable Toilets Potential harm through sewage leaks	Neg	Reversible	2	3	5	3,3	3	5	4	13,33	Med	Portable toilets will be managed by reputable contractors and inspected daily for potential leaks	1	2	3	2	2	5	3,5	7	Low- Med
Surface water	Portable Toilets Potential harm through sewage leaks	Neg	Reversible	2	3	5	3,3	3	5	4	13,33	Med	Portable toilets will be managed by reputable contractors and inspected daily for potential leaks	1	2	3	2	2	5	3,5	7	Low- Med
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg	Reversible	1	2	4	2,3	5	5	5	11,67	Medium	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.	1	1	3	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Visual aspect	Deterioration in visual aesthetics of the area	Neg	Reversible	2	1	3	2	2	5	3,5	7	Low- Med	 Visual Mitigation: The site must have a neat appearance and be kept in good condition at all times. The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. 	2	1	3	2	2	3	2,5	5	Low- Med
Soils SUB ACTIVITY	Portable Toilets Potential harm through sewage leaks Y: ACCESS ROADS	Neg	Reversible	1	3	5	3	3	5	4	12	Med	Portable toilets will be managed by reputable contractors and inspected daily for potential leaks	1	2	5	2,7	2	5	3,5	9,333	Low- Med

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Hazardous Waste	Contamination of area with hydrocarbons or hazardous waste materials	Neg F	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Contamination of surface or groundwater due to hazardous spills not cleaned: Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to ensure proper disposal. Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at a recognized facility. Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed. Suitable covered receptacles must be available at all times and conveniently placed for the disposal of waste. Non-biodegradable refuse such as glass bottles, plastic bags, metal scrap, etc., must be stored in a container with a closable lid at a collecting point, collected on a weekly basis, and disposed of at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. Biodegradable refuse generated must be handled as indicated above.	1	3	4	2,7	2	5	3,5	9,333	Low-Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles	1	3	4	2,7	2	4	3	8	Low-Med

Nature of Impact	Impact	ositive/Nega	Reversibility		ty	on	Consequence	bility	ency	poor	Significance	tion		Mitigation		ty	on	dnence	bility	ency	poor	Significance	tion
		ositiv ive/ N	Revers	Extent	Severity	Duration	Conse	Probability	requency-	Likelihood	Signifi	Mitigation	8		Extent	Severity	Duration	Consequen	Probability	requency-	Likelihood	Signifi	Mitigation Rating
											0,			and should any signs of erosion become apparent soil erosion		0,						<u> </u>	
														protection measures must be									
														implemented.									
														The effectiveness of the storm									
														water infrastructure needs to be									
														continuously monitored.									
														The activity must be conducted in accordance with the Best Practice									
														Guideline for small scale mining that									
														relates to storm water management,									
														erosion and sediment control and									
														waste management, developed by									
														the Department of Water and									
														Sanitation (DWS), and any other									
														conditions which that Department of Mineral Resources may impose:									
														o Clean water (e.g. rainwater) must									
														be kept clean and be routed to a									
														natural watercourse by a system									
														separate from the dirty water									
														system. You must prevent clean									
														water from running or spilling into									
														dirty water systems. o Dirty water must be collected and									
														contained in a system separate from									
														the clean water system.									
														o Dirty water must be prevented									
														from spilling or seeping into clean									
														water systems.									
														o Storm water management must									
														apply for the entire life cycle of the									
														site and over different hydrological cycles (rainfall patterns).									
														o The statutory requirements of									
														various regulatory agencies and the									
														interests of stakeholders must be									
														considered and incorporated into									
														the storm water management.									

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg	Reversible	1	2	4	2,3	5	5	5	11,67	Medium	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.	1	1	3	1,7	2	3	2,5	4,167	Low
Air quality	Dust nuisance caused by the disturbance of soil.	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Medium	Dust Handling: • The liberation of dust into the surrounding environment must be effectively controlled by the use of, inter alia, water spraying and/or other dust-allaying agents. • During periods of high wind spells, the stockpiles must be dampened to control dust emission. • The site manager must ensure continuous assessment of all dust suppression equipment to confirm its effectiveness in addressing dust suppression. • Speed on the access roads must be limited to 40km/h to prevent the generation of excess dust. All contractors will enforce speed limits. • Gravel roads must be sprayed with water or an environmentally friendly dust-allaying agent that contains no PCB's (e.g. DAS products) if dust is generated above acceptable limits. Roads will be sprayed with water	2	2	1	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													regularly ,especially during times of high dust generation.									
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Medium	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	3	3	4	3,3	2	1	1,5	5	Low- Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites.	3	2	4	3	1	1	1	3	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													Any leakages should be reported and treated as per the emergency response plan.									
Groundwater	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	2	3	3	2,7	3	5	4	10,67	Med	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	2	1	2	1,7	2	3	2,5	4,167	Low
SUB ACTIVITY	: SITE OFFICES			1		1		1		-		<u> </u>	_	1		1		ı	ı			
Hazardous Waste	Contamination of area with hydrocarbons or hazardous waste materials	Neg	Reversible		3	4	2,7	3	5	4	10,67	Med	Contamination of surface or groundwater due to hazardous spills not cleaned: • Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to ensure proper disposal. • Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at a recognized facility. • Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed. • Suitable covered receptacles must be available at all times and		3	4	2,7	2	5	3,5	9,333	Low- Med
													conveniently placed for the disposal of waste. • Non-biodegradable refuse such as									

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Conseduence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													glass bottles, plastic bags, metal scrap, etc., must be stored in a container with a closable lid at a collecting point, collected on a weekly basis, and disposed of at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. • Biodegradable refuse generated must be handled as indicated above.									
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large	1	3	4	2,7	2	4	3	8	Low- Med

Nature of Impact	Impact	Positive/Nega ive/ Neutral Reversibility	Extent Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
											spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the dirty water system. o Dirty water must be prevented from spilling or seeping into clean water systems. o Dirty water must be prevented from spilling or seeping into clean water systems. o Storm water management must									

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation	Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
														apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into the storm water management.									
Visual aspect	Deterioration in visual aesthetics of the area	Neg	Reversible	2	1	3	2	2	5	3,5	7	Low	ed	Visual Mitigation: • The site must have a neat appearance and be kept in good condition at all times. • The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. • Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received.	2	1	3	2	2	3	2,5	5	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.									
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg	Reversible	1	2	4	2,3	5	5	5	11,67	Medium	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.	1	1	3	1,7	2	3	2,5	4,167	Low
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment.	Neg	Reversible	3	3	4	3,3	2	1	1,5	5	Low- Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling	3	2	4	3	1	1	1	3	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Groundwater	Potential impact of mining activities on the runoff and infiltration of storm water. Potential hydrocarbon	Neg	Reversible	2	3	3	2,7	3	5	4	10,67		and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.	2	1	2	1,7	2	3	2,5	4,167	Low
	contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	J									,		contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table				,			,		
Hazardous Waste	Contamination of area with hydrocarbons or hazardous waste materials	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Contamination of surface or groundwater due to hazardous spills not cleaned: • Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to ensure proper disposal. • Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at	1	3	4	2,7	2	5	3,5	9,333	Low- Med

Environmental Impact Assessment

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
												 Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed. Suitable covered receptacles must be available at all times and conveniently placed for the disposal of waste. Non-biodegradable refuse such as glass bottles, plastic bags, metal scrap, etc., must be stored in a container with a closable lid at a collecting point, collected on a weekly basis, and disposed of at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. Biodegradable refuse generated must be handled as indicated above. 									

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles	1	3	4	2,7	2	4	3	8	Low-Med

Nature of Impact	Impact	Positive/Nega ive/ Neutral Reversibility	int	erity	Duration	Consequence	Probability	-requency	Likelihood	Significance	Mitigation Rating	Mitigation	ınt	erity	Duration	Consequence	Probability	requency_	Likelihood	Significance	Mitigation Rating
		osi ive/	xte	eve	ura	lo l	rok 	red	ike	ngis	Aitig tatii		xte	eve	Jura	on	rok	req	ike	ign	Aitiç
		Posi tive/	Extent	Severity	Dura	Con	Prob	Freq	Like	Sign	Mitig Ratii	and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water system. o Dirty water must be prevented from spilling or seeping into clean water systems. o Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into	Extent	Severity	Dura	Cons	Prob	Freq	Like	Sign Sign	Mitigati Rating
												the storm water management.									

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Visual aspect	Deterioration in visual aesthetics of the area	Neg Reversible	2	1	3	2	2	5	3,5	7	Low-Med	 Visual Mitigation: The site must have a neat appearance and be kept in good condition at all times. The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. 	2		3	2	2	3	2,5	5	Low- Med
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg Reversible	1	2	4	2,3	5	5	5	11,67	Medium	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure	1	1	3	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.									
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Medium	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	3	3	4	3,3	2	1	1,5	5	Low- Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported	3	2	4	3	1	1	1	3	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Groundwater	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through	Neg	Reversible	2	3	3	2,7	3	5	4	10,67	Med	and treated as per the emergency response plan. Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	2	1	2	1,7	2	3	2,5	4,167	Low
SUB ACTIVITY	littering leeching into the groundwater table												3 3									
Hazardous Waste	Contamination of area with hydrocarbons or hazardous waste materials	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Contamination of surface or groundwater due to hazardous spills not cleaned: Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to ensure proper disposal. Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at a recognized facility. Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed. Suitable covered receptacles must be available at all times and conveniently placed for the disposal of waste. Non-biodegradable refuse such as glass bottles, plastic bags, metal	1	3	4	2,7	2	5	3,5	9,333	Low-Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													scrap, etc., must be stored in a container with a closable lid at a collecting point, collected on a weekly basis, and disposed of at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. • Biodegradable refuse generated must be handled as indicated above.									
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large	1	3	4	2,7	2	4	3	8	Low-Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility	Extent Severity	Duration	Consequence Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
										spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water system. o Dirty water must be prevented from spilling or seeping into clean water systems. o Dirty water must be prevented from spilling or seeping into clean water systems.									

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation	Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
														apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into the storm water management.									
Visual aspect	Deterioration in visual aesthetics of the area	Neg	Reversible	2	1	3	2	2	5	3,5	7	Lov Me		Visual Mitigation: • The site must have a neat appearance and be kept in good condition at all times. • The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. • Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received.	2	1	3	2	2	3	2,5	5	Low- Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.									
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg	Reversible	1	2	4	2,3		5	5	11,67		Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.	1	1	3	1,7	2	3	2,5		
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Medium	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	3	3	4	3,3	2	1	1,5	5	Low-Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.	3	2	4	3	1	1	1	3	Low
Groundwater SUB ACTIVITY	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	2	3	3	2,7	3	5	4	10,6	7 Med	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	2	1	2	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Hazardous Waste	Contamination of area with hydrocarbons or hazardous waste materials	Neg R	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Contamination of surface or groundwater due to hazardous spills not cleaned: Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to ensure proper disposal. Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at a recognized facility. Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed. Suitable covered receptacles must be available at all times and conveniently placed for the disposal of waste. Non-biodegradable refuse such as glass bottles, plastic bags, metal scrap, etc., must be stored in a container with a closable lid at a collecting point, collected on a weekly basis, and disposed of at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. Biodegradable refuse generated must be handled as indicated above.	1	3	4	2,7	2	5	3,5	9,333	Low-Med Service Servic

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all nonrecycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles	1	3	4	2,7	2	4	3	8	Low-Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Flora	Loss of biodiversity.	Neg	Reversible	1	2	4	2,3	3	5	4	9,333		and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water system. o Dirty water must be prevented from spilling or seeping into clean water systems. o Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into the storm water management. Ensure permits are obtained to	1	4	2	2,3	2	3	2,5	5,833	Low-
1 1010	Potential damage to vegetation in neighbouring areas.		1.070101010	,	_	,	2,0			•	0,000	Med	remove protected species. Relocate all protected species with aid of specialists. Only remove species in areas	•	, 		2,0	_	3	2,0	0,000	Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility	Extent	Severity Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
	Alien invasive encroachment										designated for activity and do not disturb surrounding areas. Plan activities carefully so that only vegetation that needs to be impacted is impacted. Incorporate herbaceous vegetation into soil stockpiles to maintain a seed bank. Limit activity to area of disturbance and revegetated impacted areas as soon as possible. Eradicate and control all alien invasive species on site. Rehabilitate and revegetated all areas where alien invasive species were removed. Management of weed- or invader plants: • A weed and invader plant management plan must be implemented at the site to ensure eradication of all listed invader plants in terms of the National Environmental Biodiversity Act [NEMBA] (Act No. 10 of 2004) Alien and Invasive Species Regulation GNR 598 and 599 of 2014. • Management must take responsibility to control declared invader or exotic species on the habilitated areas. The following control methods can be used: o "The plants can be uprooted, felled or cut off and can be destroyed completely." o "The plants can be treated with an herbicide that is registered for use in connection therewith and in accordance with the directions for the use of such an herbicide." • The temporary topsoil stockpiles needs to be kept free of weeds.									

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability		Likelihood	Significance	Mitigation Rating
Visual aspect	Deterioration in visual aesthetics of the area	Neg Revers	ole 2		3	2	2	5	3,5	7	Low-Med	 Visual Mitigation: The site must have a neat appearance and be kept in good condition at all times. The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. 	2	1	3	2	2	3	2,5	5	Low- Med
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg Revers	ole 1	2	4	2,3	5	5	5	11,67	Medium	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure	1	1	3	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.									
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Medium	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	3	3	4	3,3	2	1	1,5	5	Low- Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported	3	2	4	3	1	1	1	3	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													and treated as per the emergency response plan.									
Groundwater	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	2	3	3	2,7	3	5	4	10,67	Med	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	2	1	2	1,7	2	3	2,5	4,167	Low
Hazardous Waste	Contamination of area with hydrocarbons or hazardous waste materials	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Contamination of surface or groundwater due to hazardous spills not cleaned: • Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to ensure proper disposal. • Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at a recognized facility. • Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed.	1	3	4	2,7	2	5	3,5	9,333	Low-Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													 Suitable covered receptacles must be available at all times and conveniently placed for the disposal of waste. Non-biodegradable refuse such as glass bottles, plastic bags, metal scrap, etc., must be stored in a container with a closable lid at a collecting point, collected on a weekly basis, and disposed of at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. Biodegradable refuse generated must be handled as indicated above. 									
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment	1	3	4	2,7	2	4	3	8	Low- Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
												will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water from the clean water from the clean separate from the clean water system.									

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													o Dirty water must be prevented from spilling or seeping into clean water systems. o Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into the storm water management.									
Visual aspect	Deterioration in visual aesthetics of the area	Neg	Reversible	2	1	3	2	2	5	3,5	7	Low- Med	Visual Mitigation: • The site must have a neat appearance and be kept in good condition at all times. • The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. • Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received.	2	1	3	2	2	3	2,5	5	Low- Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.									
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg	Reversible	1	2	4	2,3		5	5	11,67		Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.	1	1	3	1,7	2	3	2,5		
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Medium	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	3	3	4	3,3	2	1	1,5		Low-Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.	3	2	4	3	1	1	1	3	Low
Groundwater	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table BUNDED DIESEL AND O	Neg	Reversible	2	3	3	2,7	3	5	4	10,67	Med	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	2	1	2	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all nonrecycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles	1	3	4	2,7	2	4	3	8	Low-Med

Positive/Nega iive/Neutral Reversibility Severity Consequence	Probability Frequency Likelihood Significance Mitigation Rating	Extent Severity Duration Consequence Probability Frequency Significance Mitigation Rating
Positive/live/live/live/live/live/live/live/l	Probability Frequency Likelihood Significance Significance Mitigation Rating	and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: • Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. • Dirty water must be collected and contained in a system separate from the clean water system. • Dirty water must be prevented from spilling or seeping into clean water system. • Obry water must be prevented from spilling or seeping into clean water systems. • Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). • The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance		Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Visual aspect	Deterioration in visual aesthetics of the area		Reversible	2	1	3	2	2	5	3,5			Low- Med	Visual Mitigation: The site must have a neat appearance and be kept in good condition at all times. The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.	2	1	3	2	2	σ		5	Low-Med
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg	Reversible	1	2	4	2,3	5	5	5	11,6	67	Medium	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure	1	1	3	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.									
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	3	3	4	3,3	2	1	1,5	5	Low- Med	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	3	2	4	3	1	1	1	3	Low
Groundwater	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table Y: GENERATOR AREA (BU)	Neg	Reversible	2	3	3	2,7	3	5	4	10,67	Med	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	2	1	2	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Rev	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles	1	3	4	2,7	2	4	3	8	Low-Med

Nature of Impact	Impact	ositive/Nega	Reversibility		ity	lon	Consequence	billity	ency	poor	Significance	tion	Mitigation	t.	ity	ion	Consequence	bility	ency	poor	Significance	ition 3
		ositi ve/ N	ever	xten	ever	urati	onse	Probability	requ	ikeli	ignif	/itiga kating		xten	ever	urati	conse	roba	requency-	ikeli	ignif	Aitigation Rating
		Positi Hive/ N	Rever	Extent	Severity	Duration	Conse	Proba	Frequency	Likelihood	Signif	Mitigation Rating	and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water system. o Dirty water must be prevented from spilling or seeping into clean water systems. o Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the interact of statutory agencies and the interaction of the statutory agencies and the interaction of statutory agencies and the interaction of the statutory agencie	Extent	Severity	Duration	Consc	Probability	Frequ	Likelihood	Signif	Mitigation of the state of the
													interests of stakeholders must be considered and incorporated into the storm water management.									

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance		Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg	Reversible	1	2	4	2,3	5	5	5	11,6	67	Medium	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.	1	1	3	1,7	2	3	2,5	4,167	Low
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	3	3	4	3,3	2	1	1,5	5		Low- Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large	3	2	4	3	1	1	1	3	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.									
Groundwater	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	2	3	3	2,7	3	5	4	10,67	Med	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	2	1	2	1,7	2	3	2,5	4,167	Low
SUB ACTIVITY	: WEIGH BRIDGE																					
Hazardous Waste	Contamination of area with hydrocarbons or hazardous waste materials	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Contamination of surface or groundwater due to hazardous spills not cleaned: • Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to ensure proper disposal. • Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at a recognized facility. • Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed.	1	3	4	2,7	2	5	3,5	9,333	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Conseduence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													 Suitable covered receptacles must be available at all times and conveniently placed for the disposal of waste. Non-biodegradable refuse such as glass bottles, plastic bags, metal scrap, etc., must be stored in a container with a closable lid at a collecting point, collected on a weekly basis, and disposed of at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. Biodegradable refuse generated must be handled as indicated above. 									
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment	1	3	4	2,7	2	4	3	8	Low- Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
												will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water from the clean water systems.									

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													o Dirty water must be prevented from spilling or seeping into clean water systems. o Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into the storm water management.									
Visual aspect	Deterioration in visual aesthetics of the area	Neg	Reversible	2	1	3	2	2	5	3,5	7	Low- Med	Visual Mitigation: • The site must have a neat appearance and be kept in good condition at all times. • The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. • Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received.	2	1	3	2	2	3	2,5	5	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Extent Severity Duration Consequence Probability Frequency Significance Significance Significance
													Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg	Reversible	1	2	4	2,3	5	5	5	11,6	7 Mediu	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.
Air quality	Dust nuisance caused by the disturbance of soil.	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Mediu	 Dust Handling: The liberation of dust into the surrounding environment must be effectively controlled by the use of, inter alia, water spraying and/or other dust-allaying agents. During periods of high wind spells, the stockpiles must be dampened to control dust emission. The site manager must ensure continuous assessment of all dust suppression equipment to confirm its effectiveness in addressing dust

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													suppression. • Speed on the access roads must be limited to 40km/h to prevent the generation of excess dust. All contractors will enforce speed limits. • Gravel roads must be sprayed with water or an environmentally friendly dust-allaying agent that contains no PCB's (e.g. DAS products) if dust is generated above acceptable limits. Roads will be sprayed with water regularly ,especially during times of high dust generation.									
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Medium	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	3	3	4	3,3	2	1	1,5	5	Low- Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment	3	2	4	3	1	1	1	3	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.									
SUB ACTIVITY	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	2	3	3	2,7	3	5	4	10,67	Med	Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. All leaks will be cleaned up immediately using an absorbent material. Rigs will be regularly serviced to reduce risk of leaks. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan. Utilize water on site responsibly. Ensure all pipelines and water containment facilities are adequately sealed to prevent leaks. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company.	2	1	2	1,7	2	σ	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles	1	3	4	2,7	2	4	3	8	Low-Med

Positive/Nega ive/ Neutral Reversibility Severity Duration	Extent Severity Duration Consequence Frequency Significance Significance Rating
Positive/Iti	and should any signs of erosion become apparent soil erosion protection measures must be implemented. The effectiveness of the storm water infrastructure needs to be continuously monitored. The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, eveloped by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water system. o Dirty water must be prevented from spilling or seeping into clean water system. o Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Noise Air quality	Noise nuisance caused by machinery stripping and stockpiling the topsoil. Emissions caused by	Neg	Reversible	2	2	4	2,3	5	5	4,5	11,67	Medium	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.	2	2	3	1,7	2	3	2,5		Low
SUB ACTIVITY	vehicles and equipment												All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.									
Hazardous	C: WASTE AREA Contamination of area	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Contamination of surface or	1	3	4	2,7	2	5	3,5	9,333	Low-
Waste	with hydrocarbons or hazardous waste materials												groundwater due to hazardous spills not cleaned: • Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to									Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility	Extent Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
											 Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at a recognized facility. Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed. Suitable covered receptacles must be available at all times and conveniently placed for the disposal of waste. Non-biodegradable refuse such as glass bottles, plastic bags, metal scrap, etc., must be stored in a container with a closable lid at a collecting point, collected on a weekly basis, and disposed of at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. Biodegradable refuse generated must be handled as indicated above. 									

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles	1	3	4	2,7	2	4	3	8	Low-Med

Nature of Impact	Impact	ositive/Nega ive/ Neutral	Reversibility	ınt	Severity	Duration	Consequence	Probability	-requency	Likelihood	Significance	Mitigation Rating	Mitigation	ınt	Severity	Duration	Consequence	Probability	requency.	Likelihood	Significance	Mitigation Rating
		Pos	Rev	Extent	Sev	Dur	Cor	Pro	Fre	Like	Sign	Miti	and should any signs of erosion	Extent	Sev	Dur	Cor	Pro	Fre	Like	Sign	Mitigat Rating
				<u>Û</u>	Š	ā	Ŏ	Pı	F		is	N N N N N N N N N N N N N N N N N N N	and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water system. o Dirty water must be prevented from spilling or seeping into clean water systems. o Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the)S		Ŏ .	A P	F			M R.
													interests of stakeholders must be considered and incorporated into the storm water management.									

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility		Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Visual aspect	Deterioration in visual aesthetics of the area	Neg Re	eversible	2	1	3	2	2	5	3,5	7	Low- Med	 Visual Mitigation: The site must have a neat appearance and be kept in good condition at all times. The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. 	2	1	3	2	2	3	2,5	5	Low- Med
Fauna	Alienation of animals from the area. Potential risk to avifauna. Potential harm through littering. Loss of food, nest sites and refugia Hindrance to nocturnal animals and change in behaviour of nocturnal prey and predators. New habitat available to fauna in the area and reduced activity should	Neg Re	eversible	2	2	4	2,7	3	5	4	10,67	Med	Inform staff, contractors and visitors to not harm fauna in the area. Consider the use of bird flappers and balls on the power lines to reduce risk of birds colliding with power lines. Relocate larger animals with the aid of specialists. Ensure relevant permits are in place. Utilize directional lighting and use yellow and orange lighting where possible to reduce impacts on insects. Waste generated on site should be	2	2	4	2,7	2	5	3,5	9,333	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
	result in influx of animals to the area. Impact to nocturnal insects and their predators and other nocturnal animals.												recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Conduct annual surveys to monitor faunal biodiversity. Negative impact on fauna that may enter the area: • The site manager must ensure that no fauna is caught, killed, harmed, sold or played with. • Workers must be instructed to report any animals that may be trapped in the working area. • No snares may be set or nests raided for eggs or young.									
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	3	3	4	3,3	2	1	1,5	5	Low- Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce	3	2	4	3	1	1	1	3	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.									
Groundwater	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	2	3	3	2,7	3	5	4	10,67	Med	Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. All leaks will be cleaned up immediately using an absorbent material. Rigs will be regularly serviced to reduce risk of leaks. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan. Utilize water on site responsibly. Ensure all pipelines and water containment facilities are adequately sealed to prevent leaks. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company.	2	1	2	1,7	2	3	2,5	4,167	Low
ACTIVITY:	STRIPPING AND STOCK		G OF TOPSO	IL																		
Geology	Disturbance of geological strata	Neg	Irreversible	1	3	5	3	5	5	5	15	Medium -High	None.	1	3	5	3	5	5	5	15	Medium- High

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Hazardous Waste	Contamination of area with hydrocarbons or hazardous waste materials	Neg F	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Contamination of surface or groundwater due to hazardous spills not cleaned: Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to ensure proper disposal. Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at a recognized facility. Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed. Suitable covered receptacles must be available at all times and conveniently placed for the disposal of waste. Non-biodegradable refuse such as glass bottles, plastic bags, metal scrap, etc., must be stored in a container with a closable lid at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. Biodegradable refuse generated must be handled as indicated above.	1	3	4	2,7	2	5	3,5	9,333	Low-Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Contamination of surface or groundwater due to hazardous spills not cleaned: Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to ensure proper disposal. Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at a recognized facility. Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed. Suitable covered receptacles must be available at all times and conveniently placed for the disposal of waste. Non-biodegradable refuse such as glass bottles, plastic bags, metal scrap, etc., must be stored in a container with a closable lid at a collecting point, collected on a weekly basis, and disposed of at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. Biodegradable refuse generated must be handled as indicated above.	1	3	4	2,7	2	4	3	8	Low-Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	requency_	-ikelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	-requency	-ikelihood	Significance	Mitigation Rating
Flora	Loss of biodiversity. Potential damage to vegetation in neighbouring areas. Alien invasive encroachment	Neg	Reversible		2	4	2,3	3	5	4	9,333	Low-Med	Ensure permits are obtained to remove protected species. Relocate all protected species with aid of specialists. Only remove species in areas designated for activity and do not disturb surrounding areas. Plan activities carefully so that only vegetation that needs to be impacted is impacted. Incorporate herbaceous vegetation into soil stockpiles to maintain a seed bank. Limit activity to area of disturbance and revegetated impacted areas as soon as possible. Eradicate and control all alien invasive species on site. Rehabilitate and revegetated all areas where alien invasive species were removed. Management of weed- or invader plants: • A weed and invader plant management plan must be implemented at the site to ensure eradication of all listed invader plants in terms of the National Environmental Biodiversity Act [NEMBA] (Act No. 10 of 2004) Alien and Invasive Species Regulation GNR 598 and 599 of 2014. • Management must take responsibility to control declared invader or exotic species on the habilitated areas. The following control methods can be used: o "The plants can be uprooted, felled or cut off and can be destroyed completely." o "The plants can be treated with an herbicide that is registered for use in connection therewith and in accordance with the directions for	1	4	2	2,3	2	3	2,5	5,833	Low-Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													the use of such an herbicide." • The temporary topsoil stockpiles needs to be kept free of weeds.									
Topography	Alteration of topography	Neg	Irreversible	1	2	5	2,7	2	5	3,5	9,333	B Low- Med	Keep mining in footprint	1	2	5	2,7	2	3	2,5	6,667	Low- Med
Land Use	Veldt fire might seriously impact on surrounding land-use (livestock/irrigation of neighbouring farmers). Degrading of grazing potential for livestock farming	Neg	Reversible	1	2	2	1,7	3	5	4	6,667		Precautionary measures such as fire breaks would be taken into account and the company will join the local FPA. Should it be found that after mining operation have ceased, that the natural vegetation of the area is unacceptable, the area would be revegetated with an indigenous s grass seed mix.	1	2	2	1,7	3	3	3	5	Low- Med
Visual aspect	Deterioration in visual aesthetics of the area	Neg	Reversible	2	1	3	2	2	5	3,5	7	Low- Med	Visual Mitigation: • The site must have a neat appearance and be kept in good condition at all times. • The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. • Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting	2	1	3	2	2	3	2,5	5	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.									
Archaeological & cultural sites	Loss of and disturbance to surface archaeological sites	Neg	Irreversible	1	5	5	3,7	1	5	3	11	Med	Should artefacts or archaeological items be observed, then all activity should cease immediately, the area marked off and a specialists consulted prior to any further activity.	1	5	5	3,7	1	3	2	7,333	Low- Med
Noise	Noise nuisance caused by machinery stripping and stockpiling the topsoil.	Neg	Reversible	1	2	4	2,3	5	5	5	11,67	Medium	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.	1	1	3	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	:	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Air quality	Dust generation	Neg	Reversible	2	2	4	2,7	4	5	4,5		12	Medium	 The liberation of dust into the surrounding environment must be effectively controlled by the use of, inter alia, water spraying and/or other dust-allaying agents. During periods of high wind spells, the stockpiles must be dampened to control dust emission. The site manager must ensure continuous assessment of all dust suppression equipment to confirm its effectiveness in addressing dust suppression. Speed on the access roads must be limited to 40km/h to prevent the generation of excess dust. All contractors will enforce speed limits. Gravel roads must be sprayed with water or an environmentally friendly dust-allaying agent that contains no PCB's (e.g. DAS products) if dust is generated above acceptable limits. Roads will be sprayed with water regularly ,especially during times of high dust generation. 	2	2	1	1,7	2	3	2,5	4,167	Low
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	4	2,7	4	5	4,5	5 1	12	Medium	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	ositive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	requency_	_ikelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	-requency	-ikelihood	Significance	Mitigation Rating
Fauna	Alienation of animals from the area. Potential risk to avifauna. Potential harm through littering. Loss of food, nest sites and refugia Hindrance to nocturnal animals and change in behaviour of nocturnal prey and predators. New habitat available to fauna in the area and reduced activity should result in influx of animals to the area. Impact to nocturnal insects and their predators and other nocturnal animals.	Neg	Reversible	2	2	4	2,7	3	5	4	10,67	Med	Inform staff, contractors and visitors to not harm fauna in the area. Consider the use of bird flappers and balls on the power lines to reduce risk of birds colliding with power lines. Relocate larger animals with the aid of specialists. Ensure relevant permits are in place. Utilize directional lighting and use yellow and orange lighting where possible to reduce impacts on insects. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Conduct annual surveys to monitor faunal biodiversity. Negative impact on fauna that may enter the area: The site manager must ensure that no fauna is caught, killed, harmed, sold or played with. Workers must be instructed to report any animals that may be trapped in the working area. No snares may be set or nests raided for eggs or young.	2	2	4	2,7	2	5	3,5	9,333	Low-Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	3	3	4	3,3	2	1	1,5	5	Low-Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.	3	2	4	3	1	1		3	Low
Groundwater	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	2	3	3	2,7	3	5	4	10,67	Med	Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. All leaks will be cleaned up immediately using an absorbent material. Rigs will be regularly serviced to reduce risk of leaks. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan. Utilize water on site responsibly. Ensure all pipelines	2	1	2	1,7	2	3	2,5	4,167	Low

Environmental Impact Assessment

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility	Extent	Severity	Duration	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
OPERATIONAL	LPHASE										and water containment facilities are adequately sealed to prevent leaks. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company.									
ACTIVITY:	DRILLING AND BLASTIN	G																		

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles	1	3	4	2,7	2	3	2,5	6,667	Low-Med

Nature of	Impact	ega	>				ce				Φ		Mitigation				Ce				Ф	
Impact		ositive/Neg	Reversibility			_	Consequen	<u>i</u>	5	bo	Significance	ے				_	Consequen	Ē	cy	bo	Significance	r C
		ive	IS:	=	ļ.	ij	ed	abil	l en	ļ ģ	fice	atic		=	rit	ti or	ed	abil	nen	ļ	fica	atic
		osit/e/)	Extent	Severity	Duration	Suc	Probability	requency-	Likelihood	gni	Mitigation Rating		xtent	Severity	Duration	ons	Probability	requency	Likelihood	gni	Mitigation Rating
		<u> </u>	ř	Û	Š	۵	ŭ	4	Ē		<u>is</u>	Σਔ	and should any signs of erosion	Û	Š	۵	ŭ	4	F		S	Σਔ
													become apparent soil erosion									
													protection measures must be									
													implemented.									
													The effectiveness of the storm									
													water infrastructure needs to be									
													continuously monitored.									
													The activity must be conducted in									
													accordance with the Best Practice									
													Guideline for small scale mining that									
													relates to storm water management,									
													erosion and sediment control and									
													waste management, developed by the Department of Water and									
													Sanitation (DWS), and any other									
													conditions which that Department of									
													Mineral Resources may impose:									
													o Clean water (e.g. rainwater) must									
													be kept clean and be routed to a									
													natural watercourse by a system									
													separate from the dirty water									
													system. You must prevent clean									
													water from running or spilling into									
													dirty water systems.									
													o Dirty water must be collected and contained in a system separate from									
													the clean water system.									
													o Dirty water must be prevented									
													from spilling or seeping into clean									
													water systems.									
													o Storm water management must									
													apply for the entire life cycle of the									
													site and over different hydrological									
													cycles (rainfall patterns).									
													o The statutory requirements of									
													various regulatory agencies and the									
													interests of stakeholders must be									
													considered and incorporated into the storm water management.									
Noise	Noise nuisance	Neg	Reversible	2	2	1	1,7	1	3	2	3 333	Low	Blasting alternatives will be	2	1	1	1,3	1	3	2	2,667	Low
140130	generated by drilling	1409	11010131016	_	_	'	','	'		_	0,000	LOW	considered to reduce noise and			'	1,5	'		_	2,007	2010
	equipment and blasting												associated vibrations									
<u> </u>	- Santinonic and blasting			1	1	l	l .	<u> </u>	1				accounted vibrations	1		1	1	1	<u> </u>	<u>I</u>		

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Hazardous Waste	Contamination of area with hydrocarbons or hazardous waste materials	Neg F	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Contamination of surface or groundwater due to hazardous spills not cleaned: Regular vehicle maintenance may only take place at the workshop on site. If emergency repairs are needed on equipment not able to move to the workshop, drip trays must be present. All waste products must be disposed of in a 200 litter closed container/bin to be removed from the emergency service area to the formal workshop in order to ensure proper disposal. Any effluents containing oil, grease or other industrial substances must be collected in a suitable receptacle and removed from the site, either for resale or for appropriate disposal at a recognized facility. Spills must be cleaned up immediately to the satisfaction of the Regional Manager of DMR by removing the spillage together with the polluted soil and by disposing it at a recognized facility. Proof must be filed. Suitable covered receptacles must be available at all times and conveniently placed for the disposal of waste. Non-biodegradable refuse such as glass bottles, plastic bags, metal scrap, etc., must be stored in a container with a closable lid at a collecting point, collected on a weekly basis, and disposed of at a recognized landfill site. Specific precautions must be taken to prevent refuse from being dumped on or near the processing area. Biodegradable refuse generated must be handled as indicated above.	1	3	4	2,7	2	5	3,5	9,333	Low-Med Service Servic

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility	Extent	Severity	Duration	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Flora	Loss of biodiversity. Potential damage to vegetation in neighbouring areas. Alien invasive encroachment	Neg Reversible		4	2 2	3 2	5	3,5	8,167	Low-Med	Ensure permits are obtained to remove protected species. Relocate all protected species with aid of specialists. Only remove species in areas designated for activity and do not disturb surrounding areas. Plan activities carefully so that only vegetation that needs to be impacted is impacted. Incorporate herbaceous vegetation into soil stockpiles to maintain a seed bank. Limit activity to area of disturbance and revegetated impacted areas as soon as possible. Eradicate and control all alien invasive species on site. Rehabilitate and revegetated all areas where alien invasive species were removed. Management of weed- or invader plants: • A weed and invader plant management plan must be implemented at the site to ensure eradication of all listed invader plants in terms of the National Environmental Biodiversity Act [NEMBA] (Act No. 10 of 2004) Alien and Invasive Species Regulation GNR 598 and 599 of 2014. • Management must take responsibility to control declared invader or exotic species on the habilitated areas. The following control methods can be used: o "The plants can be uprooted, felled or cut off and can be destroyed completely." o "The plants can be treated with an herbicide that is registered for use in connection therewith and in accordance with the directions for	1	4	2	2,3	2	3	2,5	5,833	Low-Med Service Servic

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Conseduence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													the use of such an herbicide." • The temporary topsoil stockpiles needs to be kept free of weeds.									
Topography	Alteration of topography	Neg	Irreversible	1	2	5	2,7	2	5	3,5	9,333	Low- Med	Keep mining in footprint	1	2	5	2,7	2	3	2,5	6,667	Low- Med
Geology	Disturbance of geological strata	Neg	Irreversible	1	3	5	3	5	5	5	15	Med	None.	1	3	5	3	5	1	3	9	Low- Med
Land Use	Veldt fire might seriously impact on surrounding land-use (livestock/irrigation of neighbouring farmers). Degrading of grazing potential for livestock farming	Neg	Reversible	1	2	2	1,7	3	5	4	6,667	Low- Med	Precautionary measures such as fire breaks would be taken into account and the company will join the local FPA. Should it be found that after mining operation have ceased, that the natural vegetation of the area is unacceptable, the area would be revegetated with an indigenous s grass seed mix.	1	2	2	1,7	3	3	3	5	Low- Med
Visual aspect	Deterioration in visual aesthetics of the area	Neg	Reversible	2	1	3	2	2	5	3,5	7	Low- Med	Visual Mitigation: • The site must have a neat appearance and be kept in good condition at all times. • The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. • Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP	2	1	3	2	2	3	2,5	5	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.									
Archaeological & cultural sites	Loss of and disturbance to surface archaeological sites	Neg	Irreversible	1	5	5	3,7	1	5	3	11	Med	Should artefacts or archaeological items be observed, then all activity should cease immediately, the area marked off and a specialists consulted prior to any further activity.	1	5	5	3,7	1	3	2	7,333	Low- Med
Noise	Noise nuisance generated by drilling equipment and blasting	Neg	Reversible	2	2	1	1,7	1	3	2	3,333	Low	Blasting alternatives will be considered to reduce noise and associated vibrations	1	1	1	1	1	3	2	2	Low
Air quality	Dust generation	Neg	Reversible	1	2	1	1,3	1	3	2	2,667	Low	 Dust Handling: The liberation of dust into the surrounding environment must be effectively controlled by the use of, inter alia, water spraying and/or other dust-allaying agents. During periods of high wind spells, the stockpiles must be dampened to control dust emission. The site manager must ensure continuous assessment of all dust suppression equipment to confirm its effectiveness in addressing dust suppression. Speed on the access roads must be limited to 40km/h to prevent the generation of excess dust. All contractors will enforce speed limits. 	1	1	1	1	1	3	2	2	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													Gravel roads must be sprayed with water or an environmentally friendly dust-allaying agent that contains no PCB's (e.g. DAS products) if dust is generated above acceptable limits. Roads will be sprayed with water regularly ,especially during times of high dust generation.									
Fauna	Alienation of animals from the area. Potential risk to avifauna. Potential harm through littering. Loss of food, nest sites and refugia Hindrance to nocturnal animals and change in behaviour of nocturnal prey and predators. New habitat available to fauna in the area and reduced activity should result in influx of animals to the area. Impact to nocturnal insects and their predators and other nocturnal animals.	Neg	Reversible	2	2	4	2,7	3	5	4	10,67	Low-Med	Inform staff, contractors and visitors to not harm fauna in the area. Consider the use of bird flappers and balls on the power lines to reduce risk of birds colliding with power lines. Relocate larger animals with the aid of specialists. Ensure relevant permits are in place. Utilize directional lighting and use yellow and orange lighting where possible to reduce impacts on insects. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Conduct annual surveys to monitor faunal biodiversity. Negative impact on fauna that may enter the area: • The site manager must ensure that no fauna is caught, killed, harmed, sold or played with. • Workers must be instructed to	2	2	4	2,7	2	5	3,5	9,333	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation report any animals that may be	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													trapped in the working area. No snares may be set or nests raided for eggs or young.									
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	2	1	2	1,7	2	5	3,5	5,833	Low- Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.		1	2	1,7	2	3	2,5	4,167	Low
Groundwater	Potential hydrocarbon contamination leeching	Neg	Reversible	3	3	4	3,3	2	1	1,5	5	Low- Med	Truck, machinery and equipment will be regularly serviced to reduce	3	3	4	3,3	1	1	1	3,333	Low

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
	into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table												risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. All leaks will be cleaned up immediately using an absorbent material. Rigs will be regularly serviced to reduce risk of leaks. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan. Utilize water on site responsibly. Ensure all pipelines and water containment facilities are adequately sealed to prevent leaks. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company.									
Social & Safety	Health and Safety Risk by Blasting Activities. Potential danger to surrounding communities	Neg	Reversible	1	3	1	1,7	1	3	2	3,333	Low	Ensure baseline photographs are taken of all structures which may be impacted for photographic evidence prior to any blasting. Ensure procedures in place to compensate for damage. All neighbours need to be notified of each blasting activity. The R723 and N1 roads needs to be beacons off during the blasting event. Ensure that all power-related structures are adequately marked	1	3	1	1,7	1	3	2	3,333	Low

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Conseduence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation with relevant signs and warnings	Extent	Severity	Duration	Conseduence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													and fenced off.									
ACTIVITY:	EXCAVATION AND LOAI	DING C		ATES	TO	BE PI			D													
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	1469	Reversible		3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to		3	4	2,7	2	3	2,0	6,667	Low-Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral Reversibility	Extent Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
											divert runoff water away from the processing area. Site management must weekly monitor the stockpiles and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water system. o Dirty water must be prevented from spilling or seeping into clean water systems. o Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into the storm water management.									

Nature of Impact	Impact	Positive/Nega iive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Flora	Loss of biodiversity. Potential damage to vegetation in neighbouring areas. Alien invasive encroachment	Neg	Reversible	2	2	4	2,7	3	5	4	10,67	Med	Ensure permits are obtained to remove protected species. Relocate all protected species with aid of specialists. Only remove species in areas designated for activity and do not disturb surrounding areas. Plan activities carefully so that only vegetation that needs to be impacted is impacted. Incorporate herbaceous vegetation into soil stockpiles to maintain a seed bank. Limit activity to area of disturbance and revegetated impacted areas as soon as possible. Eradicate and control all alien invasive species on site. Rehabilitate and revegetated all areas where alien invasive species were removed. Management of weed- or invader plants: • A weed and invader plant management plan must be implemented at the site to ensure eradication of all listed invader plants in terms of the National Environmental Biodiversity Act [NEMBA] (Act No. 10 of 2004) Alien and Invasive Species Regulation GNR 598 and 599 of 2014. • Management must take responsibility to control declared invader or exotic species on the habilitated areas. The following control methods can be used: o "The plants can be uprooted, felled or cut off and can be destroyed completely." o "The plants can be treated with an herbicide that is registered for use in connection therewith and in accordance with the directions for	1	4	2	2,3	2	3	2,5	5,833	Low- Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Conseduence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Conseduence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													the use of such an herbicide." • The temporary topsoil stockpiles needs to be kept free of weeds.									
Geology	Disturbance of geological strata	Neg	Irreversible	1	3	5	3	5	5	5	15	Med	None.	1	3	5	3	5	1	3	9	Low- Med
Topography	Alteration of topography	Neg	Irreversible	1	2	5	2,7	2	5	3,5	9,333	Low- Med	Keep mining in footprint	1	2	5	2,7	2	3	2,5	6,667	Low-
Hazardous Waste	Dust nuisance due to loading and transportation of the material	Neg	Reversible	1	3	4	2,7	3	5	4	10,67		 Dust Handling: The liberation of dust into the surrounding environment must be effectively controlled by the use of, inter alia, water spraying and/or other dust-allaying agents. During periods of high wind spells, the stockpiles must be dampened to control dust emission. The site manager must ensure continuous assessment of all dust suppression equipment to confirm its effectiveness in addressing dust suppression. Speed on the access roads must be limited to 40km/h to prevent the generation of excess dust. All contractors will enforce speed limits. Gravel roads must be sprayed with water or an environmentally friendly dust-allaying agent that contains no PCB's (e.g. DAS products) if dust is generated above acceptable limits. 	1	3	4	2,7	2	5	3,5	9,333	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													Roads will be sprayed with water regularly ,especially during times of high dust generation.									
Land Use	Veldt fire might seriously impact on surrounding land-use (livestock/irrigation of neighbouring farmers). Degrading of grazing potential for livestock farming	Neg	Reversible	1	2	2	1,7	3	5	4	6,667	Low- Med	Precautionary measures such as fire breaks would be taken into account and the company will join the local FPA. Should it be found that after mining operation have ceased, that the natural vegetation of the area is unacceptable, the area would be revegetated with an indigenous s grass seed mix.	1	2	2	1,7	3	3	3	5	Low- Med
Visual aspect	Deterioration in visual aesthetics of the area	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Med	Visual Mitigation: • The site must have a neat appearance and be kept in good condition at all times. • The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. • Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received. Waste generated on site should be recycled as far as possible and	2	1	3	2	2	3	2,5	5	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.									
Archaeological & cultural sites	Loss of and disturbance to surface archaeological sites	Neg	Irreversible	1	5	1	2,3	1	1	1	2,333	Low	Should artefacts or archaeological items be observed, then all activity should cease immediately, the area marked off and a specialists consulted prior to any further activity.	1	4	1	2	1	1	1	2	Low
Noise	Noise nuisance generated by excavation equipment	Neg	Reversible	1	1	3	1,7	2	5	3,5	5,833	Low- Med	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act. Trucks, machinery and equipment will be regularly serviced to ensure acceptable noise levels are not exceeded. Point sources will be enclosed where possible. Silencers will be utilized where possible. Screens will be considered if I&AP complaints are received.	1	1	3	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Air quality	Dust generation	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Med	 Dust Handling: The liberation of dust into the surrounding environment must be effectively controlled by the use of, inter alia, water spraying and/or other dust-allaying agents. During periods of high wind spells, the stockpiles must be dampened to control dust emission. The site manager must ensure continuous assessment of all dust suppression equipment to confirm its effectiveness in addressing dust suppression. Speed on the access roads must be limited to 40km/h to prevent the generation of excess dust. Gravel roads must be sprayed with water or an environmentally friendly dust-allaying agent that contains no PCB's (e.g. DAS products) if dust is generated above acceptable limits. 	2	2	1	1,7	2	3	2,5	4,167	Low
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Med	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low
Fauna	Alienation of animals from the area. Potential risk to avifauna. Potential harm through littering. Loss of food, nest sites and refugia Hindrance to nocturnal animals and change in behaviour of nocturnal prey and predators. New habitat available to fauna in the area and reduced activity should	Neg	Reversible	2	2	4	2,7	3	5	4	10,6	7 Med	Inform staff, contractors and visitors to not harm fauna in the area. Consider the use of bird flappers and balls on the power lines to reduce risk of birds colliding with power lines. Relocate larger animals with the aid of specialists. Ensure relevant permits are in place. Utilize directional lighting and use yellow and orange lighting where possible to reduce impacts on insects. Waste generated on site should be	2	2	4	2,7	2	5	3,5	9,333	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
	result in influx of animals to the area. Impact to nocturnal insects and their predators and other nocturnal animals.												recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Conduct annual surveys to monitor faunal biodiversity. Negative impact on fauna that may enter the area: • The site manager must ensure that no fauna is caught, killed, harmed, sold or played with. • Workers must be instructed to report any animals that may be trapped in the working area. • No snares may be set or nests raided for eggs or young.									
Social & Safety	Unsafe working conditions for employees	Neg	Reversible	1	2	4	2,3	3	3	3	7	Low- Med	Ensure that all stuff are made aware of all working conditions on site	1	2	4	2,3	2	3	2,5	5,833	Low- Med
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	2	1	2	1,7	2	5	3,5	5,833	Med Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season.	2	1	2	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.									
ACTIVITY:	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table CRUSHING AND SCREE	Neg	Reversible	2	3	2	2,3	2	5	3,5	8,167	Low- Med	Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. All leaks will be cleaned up immediately using an absorbent material. Rigs will be regularly serviced to reduce risk of leaks. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan. Utilize water on site responsibly. Ensure all pipelines and water containment facilities are adequately sealed to prevent leaks. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company.	2	1	2	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation	Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Noise	Noise nuisance caused by crushing plant.	Neg	Reversible	2	2	4	2,7	4	5	4,5	12	Me	ed	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act.	2	1	4	2,3	3	5	4	9,333	Low- Med
Hazardous Waste	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	1	3	4	2,7	3	5	4	10,6	7 Me	ed	Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. All leaks will be cleaned up immediately using an absorbent material. Rigs will be regularly serviced to reduce risk of leaks. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan. Utilize water on site responsibly. Ensure all pipelines and water containment facilities are adequately sealed to prevent leaks. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large	1	3	4	2,7	2	5	3,5	9,333	Low-Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													leaks will be cleared by reputable oil recycling company.									
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted	1	3	4	2,7	2	3	2,5	6,667	Low- Med

Nature of Impact	Impact	Positive/Nega ive/ Neutral Reversibility	Extent	Severity Duration	Consequence	Probability	-requency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	requency_	Likelihood	Significance	Mitigation Rating
											around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water system. o Dirty water must be prevented from spilling or seeping into clean water systems. o Dirty water must be prevented from spilling or seeping into clean water systems. o Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of									

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating		Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													various regulatory agencies and the interests of stakeholders must be considered and incorporated into the storm water management.									
Visual aspect	Deterioration in visual aesthetics of the area	Neg	Reversible	2	1	3	2	2	5	3,5	7	Low- Med	Visual Mitigation: • The site must have a neat appearance and be kept in good condition at all times. • The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. • Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received.	2	1	3	2	2	3	2,5	5	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.									
Air quality	Dust generation	Neg	Reversible	2	2	1	1,7	2	5	3,5	5,833	Low- Med	Dust will be contained within the property boundaries and will therefore affect only the landowner.	2	2	1	1,7	2	3	2,5	4,167	Low
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	1	1,7	2	5	3,5	5,833	Low- Med	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low
Fauna	Alienation of animals from the area. Potential risk to avifauna. Potential harm through littering. Loss of food, nest sites and refugia Hindrance to nocturnal animals and change in behaviour of nocturnal prey and predators. New habitat available to fauna in the area and reduced activity should result in influx of animals to the area. Impact to nocturnal insects and their predators and other nocturnal animals.	Neg	Reversible	2	2	4	2,7	3	5	4	10,67	Med	Inform staff, contractors and visitors to not harm fauna in the area. Consider the use of bird flappers and balls on the power lines to reduce risk of birds colliding with power lines. Relocate larger animals with the aid of specialists. Ensure relevant permits are in place. Utilize directional lighting and use yellow and orange lighting where possible to reduce impacts on insects. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the	2	2	4	2,7	2	5	3,5	9,333	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	M.i.t.	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
														municipality. Conduct annual surveys to monitor faunal biodiversity. Negative impact on fauna that may enter the area: • The site manager must ensure that no fauna is caught, killed, harmed, sold or played with. • Workers must be instructed to report any animals that may be trapped in the working area. • No snares may be set or nests raided for eggs or young.									
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	2	1	2	1,7	2	5	3,5	5,83		Low- Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.	2	1	2	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Negative/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
ACTIVITY:	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	2	3	2	2,3	4	5		8,167	Low-Med	Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. All leaks will be cleaned up immediately using an absorbent material. Rigs will be regularly serviced to reduce risk of leaks. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan. Utilize water on site responsibly. Ensure all pipelines and water containment facilities are adequately sealed to prevent leaks. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company.	2	1	2	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles	1	3	4	2,7	2	3	2,5	6,667	Low-Med

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	ent	erity	ation	Consequence	Probability	-requency	Likelihood	Significance	gation	Mitigation	ent	erity	ation	Consequence	Probability	requency -	Likelihood	Significance	gation ng
		Positive/ New / Ne	Revers	Extent	Severity	Duration	Conse	Probab	Freque	Likelih	Signiffic	Mitigation Rating	and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: • Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. • Dirty water must be collected and contained in a system separate from the clean water system. • Dirty water must be prevented from spilling or seeping into clean water systems. • Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). • The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into the storm water management.	Extent	Severity	Duration	Conse	Probab	Freque	Likelih	Signiffic	Mitigation Rating

Nature of Impact	Impact	Positive/Nega iive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Waste Visual aspect	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	1	3	4	2,7	3	5	3.5	7	Med	Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. All leaks will be cleaned up immediately using an absorbent material. Rigs will be regularly serviced to reduce risk of leaks. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan. Utilize water on site responsibly. Ensure all pipelines and water containment facilities are adequately sealed to prevent leaks. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company.	1	3	4	2,7	2	5		9,333	Low-
Visual aspect	Deterioration in visual aesthetics of the area	Neg	Reversible	2	1	3	2	2	5	3,5	7	Low- Med	Visual Mitigation: • The site must have a neat appearance and be kept in good condition at all times. • The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. • Upon rehabilitation of the processing area all infrastructure must be removed and the area must	2	1	3	2	2	3	2,5	5	Low- Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.									
Noise	Noise nuisance caused by vehicles	Neg	Reversible	2	2	4	2,7	3	2	2,5	6,667	Low- Med	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act.	2	1	4	2,3	2	2	2	4,667	Low
Air quality	Dust generation	Neg	Reversible	2	2	1	1,7	2	5	3,5	5,833	Med	Dust will be contained within the property boundaries and will therefore affect only the landowner.	2	2	1	1,7	2	3	2,5	4,167	Low
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	1	1,7	2	5	3,5	5,833	B Low- Med	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Traffic and Safety	Road degradation. Increased potential for road incidences Potential distraction to road users	Neg	Reversible	2	2	4	2,7	3	2		6,667	Low- Med	All intersections with main tarred roads will be clearly signposted. drivers will be enforced to keep to set speed limits. Trucks will be roadworthy condition. A fund will be set aside to maintain the serviceability of the road verge where the trucks approach or depart from the main road. Ensure directional floodlights are utilized that focus light on the necessary areas and reduce light pollution to surrounding environment.	2	1	4	2,3	2	2	2	4,667	Low
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the runoff and infiltration of storm water.	Neg	Reversible	2	1	2	1,7	2	5	3,5	5,833	Low-Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.	2	1	2	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Groundwater	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table ONING PHASE	Neg	Reversible	2	3	2	2,3	2	5	_	8,167	Low- Med	Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. All leaks will be cleaned up immediately using an absorbent material. Rigs will be regularly serviced to reduce risk of leaks. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan. Utilize water on site responsibly. Ensure all pipelines and water containment facilities are adequately sealed to prevent leaks. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company.	2	1	2	1,7	2	3	2,5	4,167	Low
ACTIVITY:	SLOPING, LANDSCAPIN	G AND	REPLACEN	IENT	OF T	OPS	OIL O	VER	DIST	TURB	ED ARI	EA (FINAL	REHABILITATION)									

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Soils	Potential compaction of soils in neighbouring areas. Potential contamination through littering. Potential for loss of soil & damage to soil characteristics. Initial increased potential for loss of soils and soil erosion. Potential hydrocarbon contamination to soils.	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and revegetated with indigenous plants. Waste generated on site should be recycled as far as possible and sold/ given to interested contractors. Recycled waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recycle waste for disposal at the municipality. Vegetate rehabilitated area as soon as possible. Vegetable berms and stockpiles. Activity should be limited to area of disturbance. Where required the compacted soils should be disked to an adequate depth and re-vegetated with indigenous plants. Re-vegetate any bare soil immediately. Inspect, especially after first heavy rain falls to ensure adequate surface water drainage. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Loss of topsoil due to incorrect storm water management • Storm water must be diverted around the topsoil heaps, processing and stockpile areas to prevent erosion. • Topsoil heaps must be stockpiled along the northern and western boundaries of the study area to divert runoff water away from the processing area. Site management must weekly monitor the stockpiles	1	3	4	2,7	2	3	2,5	6,667	Low-Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation	Extent Severity Duration Consequence Probability Frequency Likelihood Significance Mitigation Rating	
Soils	Soils replaced and	Poe	Pavarsihla	1			2.7	3	5		10.6		and should any signs of erosion become apparent soil erosion protection measures must be implemented. • The effectiveness of the storm water infrastructure needs to be continuously monitored. • The activity must be conducted in accordance with the Best Practice Guideline for small scale mining that relates to storm water management, erosion and sediment control and waste management, developed by the Department of Water and Sanitation (DWS), and any other conditions which that Department of Mineral Resources may impose: o Clean water (e.g. rainwater) must be kept clean and be routed to a natural watercourse by a system separate from the dirty water system. You must prevent clean water from running or spilling into dirty water systems. o Dirty water must be collected and contained in a system separate from the clean water system. o Dirty water must be prevented from spilling or seeping into clean water systems. o Storm water management must apply for the entire life cycle of the site and over different hydrological cycles (rainfall patterns). o The statutory requirements of various regulatory agencies and the interests of stakeholders must be considered and incorporated into the storm water management.	
Soils	Soils replaced and ameliorated	Pos	Reversible	1	3	4	2,7	3	5	4	10,6	7 Med	Ensure activities occur only within the designated areas and stockpile and revegetated soil as soon as possible. Topsoil will be removed before	

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													mining activities commence and stored outside of the active mining cell.									
Flora	Loss of biodiversity. Potential damage to vegetation in neighbouring areas. Alien invasive encroachment	Neg	Reversible	1	4	2	2,3	2	5	3,5	8,167	Low-Med	Ensure permits are obtained to remove protected species. Relocate all protected species with aid of specialists. Only remove species in areas designated for activity and do not disturb surrounding areas. Plan activities carefully so that only vegetation that needs to be impacted is impacted. Incorporate herbaceous vegetation into soil stockpiles to maintain a seed bank. Limit activity to area of disturbance and revegetated impacted areas as soon as possible. Eradicate and control all alien invasive species on site. Rehabilitate and revegetated all areas where alien invasive species were removed. Management of weed- or invader plants: • A weed and invader plant management plan must be implemented at the site to ensure eradication of all listed invader plants in terms of the National Environmental Biodiversity Act [NEMBA] (Act No. 10 of 2004) Alien and Invasive Species Regulation GNR 598 and 599 of 2014. • Management must take responsibility to control declared invader or exotic species on the habilitated areas. The following control methods can be used: o "The plants can be uprooted, felled or cut off and can be destroyed completely." o "The plants can be treated with an	1	4	2	2,3	2	3	2,5	5,833	Low-Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													herbicide that is registered for use in connection therewith and in accordance with the directions for the use of such an herbicide." • The temporary topsoil stockpiles needs to be kept free of weeds.									
Topography	Alteration of topography	Neg	Irreversible	1	2	5	2,7	2	5	3,5	9,333	Low- Med	Keep mining in footprint. Excavation areas will be sloped during rehabilitation to even out depressions.	1	2	5	2,7	2	3	2,5	6,667	Low- Med
Topography	Eradication of trenches and berms. Re-contouring of area for free surface water drainage. Eradication of stockpiles	Pos	Irreversible	1	2	5	2,7	2	5	3,5	9,333	Low- Med	Monitor, especially after first heavy rain falls to ensure adequate surface water drainage	1	2	5	2,7	2	3	2,5	6,667	Low- Med
Land Use	Veldt fire might seriously impact on surrounding land-use (livestock/irrigation of neighbouring farmers). Degrading of grazing potential for livestock farming	Neg	Reversible	1	2	2	1,7	3	5	4	6,667	Low- Med	Precautionary measures such as fire breaks would be taken into account and the company will join the local FPA. Should it be found that after mining operation have ceased, that the natural vegetation of the area is unacceptable, the area would be revegetated with an indigenous s grass seed mix.	1	2	2	1,7	3	3	3	5	Low- Med

Nature of Impact	Impact	Positive/Nega tive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Visual aspect	Improved aesthetics through rehabilitation		Reversible	2	1	3	2	2	5	3,5		Low- Med	Visual Mitigation: The site must have a neat appearance and be kept in good condition at all times. The height of the stockpiles must be controlled to manage the visual impact on the surrounding environment. Upon rehabilitation of the processing area all infrastructure must be removed and the area must be returned to its prior status. Screens will be considered if I&AP complaints are received. Directional lighting and soft lighting will be utilized to ensure that only areas required to be lit are lit. screens will be considered if I&AP complains are received. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality.	2	1	3	2	2	3	2,5	5	Low- Med
Noise	Noise nuisance caused by machinery	Neg	Reversible	2	2	4	2,7	4	3	3,5	9,3	Low- Med	Noise Handling: The applicant must ensure that employees and staff conduct themselves in an acceptable manner while on site. No loud music may be permitted at the processing area. All project-associated vehicles must be equipped with silencers and maintained in a road worthy condition in terms of the Road Transport Act.	2	1	4	2,3	3	3	3	7	Low- Med

Nature of Impact	Impact	Positive/Nega ive/ Neutral	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
Air quality	Dust nuisance caused during landscaping activities	Neg	Reversible	2	2	1	1,7	2	5	3,5	5,833	Low- Med	Dust will be contained within the property boundaries and will therefore affect only the landowner.	2	2	1	1,7	2	3	2,5		Low
Air quality	Emissions caused by vehicles and equipment	Neg	Reversible	2	2	1	1,7	2	5	3,5	5,833	Low- Med	Emission Handling: All vehicles will be regularly services to ensure they are in proper working condition and to reduce risk of excessive emissions.	2	2	1	1,7	2	3	2,5	4,167	Low
Fauna	Reintroduction of fauna attracted to flora to the area	Pos	Reversible	2	2	4	2,7	3	5	4	10,67	Med	Inform staff, contractors and visitors to not harm fauna in the area. Conduct annual surveys to monitor faunal biodiversity.	2	2	4	2,7	2	5	3,5	9,333	Low- Med
Fauna	Reintroduction of fauna attracted to flora to the area	Pos	Reversible	2	1	3	2	1	5	3	6	Low- Med	Inform staff, contractors and visitors to not harm fauna in the area. Conduct annual surveys to monitor faunal biodiversity.	2	1	3	2	1	3	2	4	Low
Social & Safety	Health and safety risk posed by un-sloped areas	Neg	Reversible	1	3	4	2,7	3	3	3	8	Low- Med	Ensure that all stuff are made aware of all working conditions on site	2	1	3	2	1	3	2	4	Low
Surface water	Potential silt-loading of drainage lines, downstream and surrounding water bodies. Potential hydrocarbon contamination which may reach downstream surface water bodies. Potential surface water contamination if leaks escape into the environment. Potential impact of mining activities on the	Neg	Reversible	2	1	2	1,7	2	5	3,5	5,833	Low- Med	Ensure clean and dirty water separation and storm water management systems are established on site prior to construction taking place. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company. Inspect area for erosion and pooling and rehabilitate if necessary. Continue with surface water monitoring.	2	1	2	1,7	2	3	2,5	4,167	Low

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
	runoff and infiltration of storm water.												Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan.									
Surface water	Containment of dirty water. Improve response to issues relating to deterioration of surface water quality or quantity. free drainage resorted to area. Revegetation of disturbed areas reduces risk of silt loading on downstream water bodies. Large area of surface water runoff return to catchment	Pos	Reversible	2	3	2	2,3	2	5	3,5	8,167	Low- Med	Specialist must be consulted f issues with surface water are observed and qualities do not fall within the DWS target qualities or water qualities for livestock watering. Any affected registered water user must be compensated if levels an quality are impacted by the mining activities. Ensure water management facilities are operating adequately. Clean out silt build up over dry season. Monitor area for erosion and pooling and rehabilitate if necessary. Continue with Surface water monitoring.	2	1	2	1,7	2	3	2,5	4,167	Low
Hazardous Waste	Contamination of area with hydrocarbons or hazardous waste materials	Neg	Reversible	1	3	4	2,7	3	5	4	10,67	Med	Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. All leaks will be cleaned up immediately using an absorbent material. Rigs will be regularly serviced to reduce risk of leaks. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan. Utilize water on site responsibly. Ensure all pipelines and water containment facilities are	1	3	4	2,7	2	5	3,5	9,333	Low- Med

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													adequately sealed to prevent leaks. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. All hydrocarbons will be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company.									
Groundwater	Potential hydrocarbon contamination leeching into the water table. Reduction of local groundwater. Potential contamination through littering leeching into the groundwater table	Neg	Reversible	2	3	2	2,3	2	5	3,5	8,167	Low- Med	Truck, machinery and equipment will be regularly serviced to reduce risk of leaks. Any leakages should be reported and treated immediately in a reputable manner. For large spills Hazmat will called in. All leaks will be cleaned up immediately using an absorbent material. Rigs will be regularly serviced to reduce risk of leaks. Pans will be placed under potential leak sites. Any leakages should be reported and treated as per the emergency response plan. Utilize water on site responsibly. Ensure all pipelines and water containment facilities are adequately sealed to prevent leaks. Waste generated on site should be recycled as far as possible and sold/given to interested contractors. Recyclable waste should not be stored on site for excessive periods to reduced risk of environmental contamination. Refuse bins will be placed around site to collect all non-recyclable waste for disposal at the municipality. All hydrocarbons will	2	1	2	1,7	2	α	2,5	4,167	Low

Environmental Impact Assessment

Nature of Impact	Impact	Positive/Nega	Reversibility	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating
													be stored in mobile bunded containers fitted with taps. Bunded area will have adequate capacity to capacity to contain leaks. Large leaks will be cleared by reputable oil recycling company.									
Groundwater	Improve response to issues relating to deterioration of groundwater quality or quantity	Pos	Reversible	2	1	2	1,7	2	5	3,5	5,833	Low- Med	Specialist must be consulted f issues with groundwater are observed and qualities do not fall within the DWS target qualities or water qualities for livestock watering. Any affected registered water user must be compensated if levels an quality are impacted by the mining activities	2	1	2	1,7	2	5	3,5	5,833	Low- Med

Cumulative Impacts

Table 9: Cumulative Impact Assessment of Bloemhof Quarry

Nature of Impact	Impact	Positive/Negative/ Neutral Impact	Rever	Extent	Severity	Duration	Consequence	Probability	Frequency	Likelihood	Significance	Mitigation Rating	Mitigation	
CONSTRUCTION AND OPERATIONAL PHASES														
ACTIVITY: Utilization of haul and access roads within the mining right area														
SUB ACTIVITY: Truck and heavy machinery operations														
Traffic & Safety	Increased potential for road incidences	Neg	Reversible	2	3	1	2	3	1	2	4	Low	All intersections with main tarred roads will be clearly signposted. Drivers will be enforced to keep to set speed limits. Trucks will be in road-worthy condition with reflective strips.	
Traffic & Safety	Road degradation	Neg	Reversible	1	3	1	1.666667	2	1	1.5	2.5	Low	A fund will be set aside to maintain the serviceability of the road verge where the trucks approach or depart from the main road.	

Environmental Impact Assessment